

FEATURE

- Tiny and light with thick film technology.
- Higher Max. Working Voltage than general purpose series.
- Excellent Antistatic property.
- RoHS complaint.
- Compatible with Reflow and Wave soldering type
- Applications
 - Adapters
 - Industrial control system
 - Outdoor equipment
 - Medical devices
 - etc.

MANUFACTURER PART NO.

For example: ED1206J100KT5G00 - ED1206 ±5% 100KΩ T/R-5000

Series	Size	Tol.	Nominal Resistance Value	PKG	SPQ	Feature	TCR
2 codes	4 codes	1 code	2~5 codes	1 code	1 code	1 code	2 codes
ED	1206	F	100K	T	5	G	00
Anti-ESD Thick Film Chip Resistors	0201 0402 0603 0805 1206 1210	F=±1% J=±5%	1R ¹ =1Ω 4R7=4.7Ω 4K7 ² =4.7KΩ 100K=100KΩ 4M7 ³ =4.7MΩ	T=T/R ⁴	4=4K 5=5K A=10K B=15K	G=Std. S=P.C. ⁵	00=Refer to table as below.


Note: ① R=Radix, 10⁰, Ω ② K=Kilo, 10³, KΩ ③ M=Mega, 10⁶, MΩ
 ④ T/R=Taping in Reel Package. ⑤ P.C.=Personal and Customized.

CHARACTERISTICS

Series	Rated Power	MWV ^①	MOV ^②	DWV ^③	Tolerance	Resistance Value Range
ED0201	1/20W	25V	50V	-	±1%, ±5%	1Ω-10MΩ
ED0402	1/16W	50V	100V	100V	±1%, ±5%	1Ω-10MΩ
ED0603	1/4W	150V	200V	300V	±1%, ±5%	1Ω-10MΩ
ED0805	2/5W	200V	400V	500V	±1%, ±5%	1Ω-10MΩ
ED1206	2/3W	500V	1000V	500V	±1%, ±5%	1Ω-10MΩ
ED1210	1/2W	800V	1500V	500V	±1%, ±5%	1Ω-10MΩ

Note: ① MWV=Max. Working Voltage. ② MOV=Max. Overload Voltage. ③ DWV=Dielectric Withstanding Voltage

POWER DERATING CURVE



Note: Operating temperature range is from -55°C to +155°C

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, <http://www.giantohm.com/download/cid/22.html>

RATED VOLTAGE

Resistors should have a Rated Voltage DC or AC corresponding to Rated Power which can be calculated by formula as below.







The Rated Voltage of certain resistance value should be the calculated result or Max. Working Voltage of product series whichever less.

Formula:

$$E = \sqrt{P \times R}$$

E=Rated voltage(V)
 P=Rated power(W)
 R=Nominal resistance(Ω)

ESD LIMITING VOLTAGE CURVE



Note: HBM:100PF 1K5 1Cycle MM: 200PF 0E 1Cycle

ED Series

Anti-ESD Thick Film Chip Resistors

Version. A



DIMENSIONS

Unit: mm

Figure	Type	L	W	H	A	B
	ED0201	0.60±0.03	0.30±0.03	0.23±0.03	0.10±0.05	0.15±0.05
	ED0402	1.00±0.10	0.50±0.05	0.35±0.05	0.20±0.10	0.25±0.10
	ED0603	1.60±0.10	0.80±0.10	0.45±0.10	0.30±0.20	0.30±0.20
	ED0805	2.00±0.15	1.25±0.15	0.55±0.10	0.40±0.20	0.40±0.20
	ED1206	3.10±0.15	1.55±0.15	0.55±0.10	0.45±0.20	0.45±0.20
	ED1210	3.10±0.10	2.60±0.20	0.55±0.10	0.50±0.25	0.50±0.20

RELIABILITY

Item	Test Method	Acceptable criterion
Temperature Coefficient of Resistance (T.C.R.)	$TCR(PPM/^{\circ}C) = \frac{(R_2 - R_1)}{R_1 \times (T_2 - T_1)} \times 10^6$ <p> R_1=Value in room temperature R_2=Value in test temperature -55°C or +125°C T_1=Room temperature T_2=Test temperature -55°C or +125°C Reference: IEC 60115-1 6.2 </p>	ED0201: $1\Omega \leq R \leq 10\Omega$: +400PPM/°C $> 10\Omega$: ±200PPM/°C ED0402~1210: $1\Omega \leq R \leq 10\Omega$: ±200PPM/°C $> 10\Omega$: ±100PPM/°C
Insulation Resistance	Using the parallel clamp method: 100±15V _{DC} voltage is applied between the electrode and the substrate within 60 seconds. Test the insulation resistance between the terminal and the back of the part. Reference: IEC 60115-1 12.1.3.5	$\geq 10^9 \Omega$
Dielectric Withstanding Voltage	An alternating current with an effective value of the maximum overload voltage is applied between the electrode and the substrate at a rate of approximately 100V/sec. Pressure, maintain 60± 5 sec. The test voltage reference to the DWV in characteristics. Reference: IEC 60115-1 12.2.4	Test to confirm if the presence of current or arc breakdown by $\geq 10\mu A$
Short Time Over Load	Apply 2.5 times of rated voltage or maximum overload voltage (whichever is the smallest) for 5 seconds Reference: IEC 60115-1 8.1.4.2	1% series: $\Delta R/R = \pm 1.0\%$ 5% series: $\Delta R/R = \pm 2.0\%$
Intermittent Overload	Put it in the thermostat, apply 2.5 times of rated voltage, 1 second ON, 25 seconds OFF, 10000 ⁺⁴⁰⁰ ₀ cycles, take it out and stand for 60 minutes, then measure the change rate of resistance value. Reference: IEC 60115-1 8.4.4	$\Delta R/R = \pm 5.0\%$
Resistance to Solvent	Immerse in isopropanol solvent at room temperature (23±5°C) for 5min, wipe 10 times with a hard toothbrush, repeat 3 times, take out and blow dry for examination Reference: IEC 60115-1 11.3.2 method1	No obvious damage, peeling, swelling phenomenon
Solderability	Pretreatment: dry heat 155°C, 4 hrs. or PCT aging for 4 hrs. (equivalent), after take out, stand at room temperature for 2 hrs. Test method: 1. Dip the resistance in a tin furnace at 245±3°C for 3 seconds, then take it out and observe the solder area under a microscope; 2. Reflow soldering test, Peak Temperature: 235°C, T=40±5 sec. Reference: IEC 60115-1 11.1.4.3	1. Solder coverage over 95% 2. No welding refusal phenomenon, side soldering height is greater than 1/2 of the height
Leaching	Pretreatment: dry heat 155°C, 4 hrs. or PCT aging for 4 hrs. (equivalent), after take out, stand at room temperature for 2 hrs. dip in a tin furnace at 260±5°C for 30±1 seconds, remove and wash. Observe the area of solder under a microscope Reference: IEC-60068-2-58	No electrode is eroded to expose the substrate phenomenon

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, <http://www.giantohm.com/download/cid/22.html>

ED Series

Anti-ESD Thick Film Chip Resistors



Version. A



Item	Test Method	Acceptable criterion										
Resistance to Soldering Heat	The tested resistor be immersed into molten solder of $260 \pm 5^{\circ}\text{C}$ for 10 seconds. Then the resistor is left in the room for 1 hr., then measure the change rate of resistance value Reference: IEC 60115-1 11.2.4.3	$\Delta R/R = \pm 1.0\%$										
Thermal Shock	High and low temperature test is carried out according to the upper and lower limits of the application temperature of the parts, the residence time of the upper and lower limits of the temperature is 30min, and the temperature conversion time is less than 30s, lasting 500 cycles Reference: IEC 60115-1 10.1.4	$\Delta R/R = \pm 1.0\%$										
Solder Joint Endurance Test	The SMD resistance was welded to the test board and bent with the standard pressure block. After standing for 60 sec. under the corresponding deformation condition, the change rate of resistance value of the part was tested. <table border="1"> <tr> <td>Size</td> <td>0402, 0603, 0805</td> <td>0201, 1206, 1210</td> </tr> <tr> <td>Depth</td> <td>5mm</td> <td>3mm</td> </tr> </table> Reference: IEC 60115-1 9.8.4	Size	0402, 0603, 0805	0201, 1206, 1210	Depth	5mm	3mm	$\Delta R/R = \pm 1.0\%$				
Size	0402, 0603, 0805	0201, 1206, 1210										
Depth	5mm	3mm										
Resistance to Dry Heat	Put it in an oven at $155 \pm 5^{\circ}\text{C}$ for 1000_{-0}^{+48} hrs., take it out and let it stand for more than 1hr., then measure the change rate of resistance value Reference: IEC 60115-1 7.3	1% series: $\Delta R/R = \pm 1.0\%$ 5% series: $\Delta R/R = \pm 3.0\%$										
Loading Life in Moisture	Place it in a constant temperature and humidity box with $40 \pm 2^{\circ}\text{C}$ and 90–95%RH and apply the rated voltage with 90 minutes ON and 30 minutes OFF, 1000 hrs. Take it out and stand for 60 minutes, and then measure the change rate Reference: IEC 60115-1 10.4	1% series: $\Delta R/R = \pm 1.0\%$ 5% series: $\Delta R/R = \pm 3.0\%$										
Load Life	Put in an oven at $70 \pm 2^{\circ}\text{C}$, apply rated voltage, 90 min ON, 30 min OFF, 1000 hrs., take out and stand for more than 60 min, then measure the resistance change rate. Reference: IEC 60115-1 7.1	1% series: $\Delta R/R = \pm 1.0\%$ 5% series: $\Delta R/R = \pm 3.0\%$										
Low temperature load test	-55°C , unpowered, 1 hr.: Rated voltage/current for 45 minutes, then unpowered within 15 minutes, return to room temperature, take out and stand for 24 hours, then measure the change rate of resistance value. Reference: IEC 60115-1 10.2.4	1% series: $\Delta R/R = \pm 1.0\%$ 5% series: $\Delta R/R = \pm 2.0\%$										
Shear force test	Weld the part to the PCB. Apply the corresponding test stress from the side of the part with the test terminal for 10s. Check the appearance of the welded end of the part under the stress condition <table border="1"> <tr> <td>Size</td> <td>0201</td> <td>0402, 0603</td> <td>0805</td> <td>1206, 1210</td> </tr> <tr> <td>Test force</td> <td>2N</td> <td>5N</td> <td>9N</td> <td>25N</td> </tr> </table> Reference: IEC 60115-1 9.7	Size	0201	0402, 0603	0805	1206, 1210	Test force	2N	5N	9N	25N	Without obvious damage.
Size	0201	0402, 0603	0805	1206, 1210								
Test force	2N	5N	9N	25N								
ESD	Put the specimens with voltage in test machine, and the voltage shall be set up as following table. Test method: Electro-Static discharges twice which positive and negative polarity once each by human body mode. <table border="1"> <tr> <td>Size</td> <td>0201</td> <td>0402, 0603</td> <td>0805, 1206, 1210</td> </tr> <tr> <td>Voltage</td> <td>500V</td> <td>1,000V</td> <td>2,000V</td> </tr> </table> AEC-Q200 Test 17, AEC-Q200-002	Size	0201	0402, 0603	0805, 1206, 1210	Voltage	500V	1,000V	2,000V	$\Delta R/R = \pm 2.0\%$		
Size	0201	0402, 0603	0805, 1206, 1210									
Voltage	500V	1,000V	2,000V									


SOLDERING TEMPERATURE

• Recommendation only. Please adjust it according to the actual application

Lead-free IR Reflow Soldering Profile	Lead-free Double-Wave Soldering Profile
	
<p>Note:</p> <ul style="list-style-type: none"> • The Max. Temp. is $260 \pm 5^{\circ}\text{C}$ within 10 sec • Reference: J-STD-020D 	<p>Note:</p> <ul style="list-style-type: none"> • Suit for ≥ 0603 size • Manual soldering in $350 \pm 10^{\circ}\text{C}$ within 3 sec.

SOLDERING PAD

Resistance value would be lower than nominal value because of joint with soldering material, so designing circuit should adjust the pad size



Unit: mm

Type	A	B	C
ED0201	0.3	1.0	0.4
ED0402	0.5	1.5	0.6
ED0603	0.8	2.1	0.9
ED0805	1.2	3.0	1.3
ED1206	2.2	4.2	1.6
ED1210	2.2	4.2	2.8

WORKING ENVIRONMENT

If user intends to use products in special environments or states (including but not limited to the following), it is necessary to approve special characteristics and reliability for the following or other application environments.

- High temperature, high moisture.
- Near the sea, or corrosive gas, such as Cl_2 , H_2S , NH_3 , SO_2 and NO_2 , etc.
- Unverified liquids, such as water, oil, chemical or organic solvent.
- Unverified resin or paint to cover products.
- Products should be washed with water soluble cleaner even if non cleaning flux.

STORAGE / CARRY CONDITIONS

- Temperature: $25 \pm 5^{\circ}\text{C}$
- Humidity: $60 \pm 15\% \text{RH}$
- Storage life: 0201 size: 1 year; ≥ 0402 size: 2 years. FIFO.
- Please hold box correct orientation when storing and carrying. It is strictly prohibited to fall or squeeze the box, otherwise the product electrode or body may be damaged.

LEGAL DISCLAIMER

GiantOhm and its distributors or agents (hereinafter referred to as GiantOhm) shall not bear any responsibility for any error, inaccuracy or incompleteness contained in any product related information (including but not limited to product specifications, data, pictures, and charts). GiantOhm may change, revise, or improve product related information at any time without prior notice.

GiantOhm makes no commitment, guarantee for the suitability of its products for special purposes or the continuous production of any of its products. To the maximum extent permitted by law, GiantOhm does not assume any of the following responsibilities:

- A. All liabilities arising from the application or use of any GiantOhm's products.
- B. All liabilities, including but not limited to the loss of profits or direct damage, indirect damage, special damage, punitive damage, derivative damage, or incidental damage caused by or related to GiantOhm's products.
- C. All implied warranties, including fitness for a particular purpose, non-infringement, and merchantability.

GiantOhm defines this product as a general consumer electronic purpose, which is not applicable to any medical lifesaving or life-sustaining equipment, nor to any application that may cause casualties in case of failure of GiantOhm's products.

All technical suggestions on product application provided by GiantOhm are provided free of charge. GiantOhm assumes no obligation and responsibility for adopting such technical suggestions and available results, and all risks of adopting such suggestions shall be borne by the buyer. All risks and responsibilities arising from the buyer's use of GiantOhm's products in combination with other materials or raw materials, or in any combination in its manufacturing process, shall be borne by the buyer, regardless of any oral or written technical instructions, suggestions or other requirements given by GiantOhm for the use of the products.

The information provided above is only to explain the product specifications. If the product is not changed, GiantOhm has all the rights to modify the above contents without prior notice, and the product change will be notified to the customer by ECN.

