FEATURE

- Tiny and light with thick film technology.
- Low temperature coefficient narrow to 50 PPM/℃
- RoHS and Halogen-free compliance
- High reliability and stability.
- Compatible with Reflow and Wave soldering type
- Applications:
  - Cell phone
  - Computer, notebook, workstation, tablet, and peripherals
  - Instruments and meters
  - etc.

MANUFACTURER PART NO.

For example: LC1206J100KT5G00-LC1206 ±5% 100KΩ T/R-5000 50PPM/℃

Series	Size	Tol.	Resistance Value	PKG	SPQ	Feature	TCR
2 codes	4 codes	1 code	2~5 codes	1 code	1 code	1 code	2 codes
LC	1206	F	100K	T	5	G	00
Low temperature coefficient thick film chip resistors	0402 0603 0805 1206	C=0.25% D=0.5% F=1%	1R①=1Ω 4R7=4.7Ω 4K7②=4.7KΩ 100K=100KΩ 1M③=1MΩ	T=T/R④	4=4K 5=5K A=10K	G=Std. S=P.C.⑤	25⑥=25PPM/℃ 00=Refer to table as below.

Note: ① R=Radix, 10^0, Ω ② K=Kilo, 10^3, KΩ ③ M=Mega, 10^6, MΩ
④ T/R=Taping in Reel Package. ⑤ P.C.=Personal and Customized. ⑥ Clod T.C.R(-55℃/+25℃)为-50~+25PPM/℃


CHARACTERISTICS

Item	Rated Power	MWV①	MOV②	TCR ppm/℃	Value Range		
					±0.25%	±0.5%	±1%
LC0402	1/16W	50V	100V	±50	100Ω~1MΩ	100Ω~1MΩ	100Ω~1MΩ
LC0402	1/16W	50V	100V	-50~+25	300Ω~1MΩ	300Ω~1MΩ	300Ω~1MΩ
LC0603	1/10W	75V	150V	±100	1Ω~10Ω	1Ω~10Ω（含）	1Ω~10Ω（含）
LC0603	1/10W	75V	150V	±50	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ
LC0603	1/10W	75V	150V	-50~+25	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ
LC0805	1/8W	150V	300V	±100	1Ω~10Ω	1Ω~10Ω（含）	1Ω~10Ω（含）
LC0805	1/8W	150V	300V	±50	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ
LC0805	1/8W	150V	300V	-50~+25	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ
LC1206	1/4W	200V	400V	±100	1Ω~10Ω	1Ω~10Ω（含）	1Ω~10Ω（含）
LC1206	1/4W	200V	400V	±50	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ
LC1206	1/4W	200V	400V	-50~+25	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ	10Ω（不含）~1MΩ

Note: ① MWV=Max. Working Voltage. ② MOV=Max. Overload Voltage.

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html

POWER DERATING CURVE



Note: Operating temperature range is from -55℃ to +155℃

RATED VOLTAGE

Resistors should have a Rated Voltage DC or AC corresponding to Rated Power which can be calculated by formula as below.

The Rated Voltage of certain resistance value should be the calculated result or Max. Working Voltage of product series whichever less.


Formula:

$$E = \sqrt{P \times R}$$

E=Rated voltage(V)
P=Rated power(W)
R=Nominal resistance(Ω)

DIMENSIONS

Unit: mm

Figure	Type	L	W	H	A	B
	LC0402	1.00±0.10	0.50±0.05	0.35±0.05	0.20±0.10	0.25±0.10
	LC0603	1.60±0.10	0.80±0.10	0.45±0.10	0.30±0.20	0.30±0.20
	LC0805	2.00±0.15	1.25±0.15	0.55±0.10	0.40±0.20	0.40±0.20
	LC1206	3.10±0.10	1.55±0.15	0.55±0.10	0.45±0.20	0.45±0.20

RELIABILITY

Item	Test Method	Acceptable criterion
Temperature Coefficient of Resistance (T.C.R.)	$TCR(PPM/℃)=\frac{(R_2-R_1)}{R_1\times(T_2-T_1)}\times10^6$ R_1=Value in room temperature R_2=Value in test temperature -55℃ or +125℃ T_1 =Room temperature T_2 =Test temperature -55℃ or +125℃ **Reference: IEC 60115-1 6.2**	reference characteristics
Insulation Resistance	Using the parallel clamp method: 100±15V_{DC} voltage is applied between the electrode and the substrate within 60 seconds. Test the insulation resistance between the terminal and the back of the part. **Reference: IEC 60115-1 12.1.3.5**	⩾ 10^9Ω

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html



Item	Test Method	Acceptable criterion
Dielectric Withstanding Voltage	An alternating current with an effective value of the maximum overload voltage is applied between the electrode and the substrate at a rate of approximately 100V/s Pressure, maintain 60s± 5S. The test voltage reference to the DWV in characteristics. **Reference: IEC 60115-1 12.2.4**	Test to confirm if the presence of current or arc breakdown by ⩾10uA
Short Time Over Load	Apply 2.5 times of rated voltage or maximum overload voltage whichever is less for 5 seconds **Reference: IEC 60115-1 8.1.4.2**	1% series: △R/R=±1.0% 5% series: △R/R=±2.0%
Intermittent Overload	Put it in the thermostat, apply 2.5 times rated voltage, 1 second ON, 25 seconds OFF, count 10000^{+400}_{0} times, take it out and stand for 60 minutes, then measure the change rate of resistance value. **Reference: IEC 60115-1 8.4.4**	△R/R=±5.0%
Resistance to Solvent	Immerse in isopropanol solvent at room temperature (23±5) for 5min, wipe 10 times with a hard toothbrush, repeat 3 times, take out and blow dry for examination **Reference: IEC 60115-1 11.3.2 method1**	No obvious damage, peeling, swelling phenomenon
Solderability	Pretreatment: dry heat 155℃, 4 hrs. or PCT aging for 4 hrs. (equivalent), after take out, stand at room temperature for 2 hrs. Test method: 1. Dip the resistance in a tin furnace at 245±3℃ for 3 seconds, then take it out and observe the solder area under a microscope; 2. Reflow soldering test, Peak Temperature: 235℃, T=40±5 sec. **Reference: IEC 60115-1 11.1.4.3**	1. Solder coverage over 95% 2. No welding refusal phenomenon, side soldering height is greater than 1/2 of the height
Leaching	Pretreatment: dry heat 155℃, 4 hrs. or PCT aging for 4 hrs. (equivalent), after take out, stand at room temperature for 2 hrs. dip in a tin furnace at 260^{+5}_{0} ℃ for 30^{+1}_{0} seconds, remove and wash. Observe the area of solder under a microscope **Reference: IEC-60068-2-58**	No electrode is eroded to expose the substrate phenomenon
Resistance to Soldering Heat	The tested resistor be immersed into molten solder of 260^{+5}_{0} ℃ for 10 seconds. Then the resistor is left in the room for 1 hour, then measure the change rate of resistance value **Reference: IEC 60115-1 11.2.4.3**	△R/R=±1.0%
Thermal Shock	High and low temperature test is carried out according to the upper and lower limits of the application temperature of the parts, the residence time of the upper and lower limits of the temperature is 30min, and the temperature conversion time is less than 30s, lasting 500 cycles **Reference: IEC 60115-1 10.1.4**	△R/R=±1.0%
Solder Joint Endurance Test	The SMD resistance was welded to the test board and bent with the standard pressure block. After standing for 60s under the corresponding deformation condition, the change rate of resistance value of the part was tested. Size: 0402, 0603, 0805 | 0201, 1206, 1210 | 2010, 2512 Depth: 5mm | 3mm | 2mm **Reference: IEC 60115-1 9.8.4**	△R/R=±1.0%
Resistance to Dry Heat	Put it in an oven at 155±5℃ for 1000^{+48}_{0} hrs., take it out and let it stand for more than 1hr., then measure the change rate of resistance value **Reference: IEC 60115-1 7.3**	1% series: △R/R=±1.0% 5% series: △R/R=±3.0%
Loading Life in Moisture	Place it in a constant temperature and humidity box with 40±2℃ and 90~95%RH and apply the rated voltage, on for 90 minutes and off for 30 minutes, a total of 1000 hours. Take it out and stand for 60 minutes, and then measure the change rate **Reference: IEC 60115-1 10.4**	1% series: △R/R=±1.0% 5% series: △R/R=±3.0%

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html

Item	Test Method	Acceptable criterion
Load Life	Put in an oven at 70±2℃, apply rated voltage, 90 min ON, 30 min OFF, 1000 hrs., take out and stand for more than 60 min, then measure the resistance change rate. **Reference: IEC 60115-1 7.1**	1% series: △R/R=±1.0% 5% series: △R/R=±3.0%
Low temperature load test	-55℃ unpowered for 1 hour: rated voltage/current for 45 minutes, unpowered for 15 minutes, return to room temperature, take out and stand for 24 hours, then measure the change rate of resistance value. **Reference: IEC 60115-1 10.2.4**	1% series: △R/R=±1.0% 5% series: △R/R=±2.0%
Shear force test	Weld the part to the PCB. Apply the corresponding test stress from the side of the part with the test terminal for 10s. Check the appearance of the welded end of the part under the stress condition Size: 0201 | 0402, 0603 | 0805 | 1206, 1210 | 2010, 2512 Test force: 2N | 5N | 9N | 25N | 45N **Reference: IEC 60115-1 9.7**	Without obvious injury

SOLDERING TEMPERATURE


- Recommendation only. Please adjust it according to the actual application

Lead-free IR Reflow Soldering Profile	Lead-free Double-Wave Soldering Profile
	
Note: • The Max. Temp. is 260^{+5}_{0}℃ within 10 sec • Reference: J-STD-020D	Note: • Suit for ⩾ 0603 size • Manual soldering in 350±10℃ within 3 sec.

SOLDERING PAD

Resistance value would be lower than nominal value because of joint with soldering material, so designing circuit should adjust the pad size

Unit: mm

Figure	Type	A	B	C
	LC0402	0.5	1.5	0.6
	LC0603	0.8	2.1	0.9
	LC0805	1.2	3.0	1.3
	LC1206	2.2	4.2	1.6

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html

WORKING ENVIRONMENT

If user intends to use products in special environments or states (including but not limited to the following), it is necessary to approve special characteristics and reliability for the following or other application environments.

A. High temperature, high moisture.
B. Near the sea, or corrosive gas, such as Cl_2, H_2S, NH_3, SO_2 and NO_2, etc.
C. Unverified liquids, such as water, oil, chemical or organic solvent.
D. Unverified resin or paint to cover products.
E. Products should be washed with water soluble cleaner even if non cleaning flux.

STORAGE / CARRY CONDITIONS

A. Temperature: 25±5℃
B. Humidity: 60±15%RH
C. Storage life: 2 years. FIFO.
D. Please hold box correct orientation when storing and carrying. It is strictly prohibited to fall or squeeze the box, otherwise the product electrode or body may be damaged.

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html

LEGAL DISCLAIMER

1. **Right to Modify Information**
   - NingBo Giantohm Micro Electronics Technology Co., Ltd. (hereinafter referred to as Giantohm, including distributors and agents, the same applies hereinafter) retains the right to interpret, update, and revise product information (specifications, data, images, etc.).
   - Product information shall be subject to the published version on GiantOhm official website (www.giantohm.com). Please note to check for updates.
2. **Limitation of Liability**

   To the maximum extent permitted by applicable laws, GiantOhm shall not be liable for:
   - **Misuse Liability**: All liabilities arising from improper use or application of the products.
   - **Damages**: Any direct/indirect losses (including loss of profit, special damages, punitive damages, etc.) caused by improper use or application of the products, regardless of the legal theory (contract, tort, or otherwise).
   - **Implied Warranties**: Exclusion of implied fitness warranties for a particular purpose, non-infringement, and merchantability (except as mandated by law).
3. **Product Use Scope and Technical Advice Liability**
   - Statements regarding the suitability of products for certain types of applications are based on GiantOhm knowledge of typical requirements that are often placed on GiantOhm products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the user's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.
   - Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each user application by the user's technical experts for the application, with the user assuming full responsibility.
   - Except as expressly indicated in writing, GiantOhm products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the GiantOhm product could result in personal injury or death. users using or selling GiantOhm products not expressly indicated for use in such applications do so at their own risk.
4. **Combined Use Risk**
   - When the product is used in combination with other materials or processes, the Buyer assumes all risks and liabilities. GiantOhm does not warrant the suitability of the combination and shall not be liable for any responsibilities.
5. **Disclaimer Updates**
   - The updated Terms shall prevail over previous versions and shall be subject to the latest version published on the official website (http://www.giantohm.com/download/cid/22.html), except for transactions concluded prior to the effective date of the amendments.
   - Continued use of the products by the user after the Terms update shall constitute deemed acceptance of the new Terms.
6. **Effectiveness:**
   - This disclaimer does not exclude liability for personal injury caused by intentional misconduct or gross negligence, or other liabilities prohibited from exclusion by law.

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html

VERSION HISTORY

Version	Date	Change Item(s)	Description
A	2022/05/25	-	First version
B	2022/10/31	-	Updated test items, method and acceptable criterion.
C	2025/04/08	Legal Disclaimer	Revise the entire text
D	2025/04/25	Feature	RoHS
E	2025/10/27	Manufactuere Part No	Increase the 25 PPM
F	2026/07/29	characteristics	Updated TCR for each resistance segment

This document is subject to change without notice. The products described herein, and this document are subject to specific disclaimers, set forth at GiantOhm official website, http://www.giantohm.com/download/cid/22.html